

PORTABLE AIR CONDITIONERS

ZICO



- Ecological refrigerant R290
- Electrostatic HD iAIR filter
- Airflow control system eMOTO
- Wide angle air flow eMOTO
- Remote controller
- Louver settings memory
- Refrigerant leak alarm
- Auto restart memory
- Anti-corrosive gold-plated fins
- Timer
- Automatic evaporation
- Self-diagnosis function
- Automatic louver
- Sleep function



TECHNICAL DATA

Model				Zico 3.5 kW
Capacity	Cooling	Nominal	W	3517
Power consumption		Nominal	W	1350
Operating current		Nominal	A	5.9
Capacity	Heating	Nominal	W	2931
Power consumption		Nominal	W	1045
Operating current		Nominal	A	5.0
Energy efficiency class - cooling				A
Energy efficiency class - heating				A+
EER / COP			W / W	2.6 / 2.8
Dehumidification			l/h	3.2
Indoor unit				Z35W
Fan speed		(Hi./Mi./Lo.)	rpm	760/690/650
Air flow		(Hi./Mi./Lo.)	m³/h	420/370/355
Sound pressure level at standard rating conditions		(Hi./Mi./Lo.)	dB(A)	53/52/51
Sound power level at standard rating conditions			dB(A)	63
Net Dimensions		(W×D×H)	mm	467×397×765
Gross dimensions		(W×D×H)	mm	515×440×890
Net weight / Gross weight			kg	34.4/37.8
Compressor type				Rotary DC
Refrigerant	Type			R290
	GWP			3
	Amount of refrigerant	kg		0.23
TCO ₂ eq			0.0	
Condensate drain				mm
Power supply indoor unit				V-Hz, Ø
Overcurrent protection				A
Inside working range				(Cooling/Heating) °C
				17-35/5-30